

# **Custom Pipe Marking**

- Order check list









Order only the best pipe markers for your environment. Carefully consider the options below for maximum durability and return on investment. Contact Brady for more support.

### Available materials:

	INDOOR	OUTDOOR	OUTDOOR+
With adhesive	<ul> <li>B-7543P</li> <li>Indoor application</li> <li>No laminate</li> <li>Low UV-resistance</li> <li>Medium scratch resistance</li> <li>Medium chemical resistance</li> <li>-40°C to +120°C</li> <li>3 to 5 year durability</li> </ul>	<ul> <li>B-7541P*</li> <li>Outdoor application</li> <li>Laminated</li> <li>Good UV-resistance</li> <li>High scratch resistance</li> <li>Good chemical resistance</li> <li>-40°C to +120°C</li> <li>Up to 5 year durability</li> </ul>	<ul> <li>B-7529P</li> <li>Outdoor application</li> <li>Laminate with UV blocker</li> <li>High UV stability</li> <li>High scratch resistance</li> <li>Good chemical resistance</li> <li>-40°C to +120°C</li> <li>Up to 10 year durability</li> </ul>
Without adhesive	<ul> <li>B-7560P</li> <li>Indoor application</li> <li>No laminate</li> <li>Low UV-resistance</li> <li>Medium scratch resistance</li> <li>Medium chemical resistance</li> <li>- 40°C to +120°C</li> <li>3 to 5 year durability</li> </ul>	<ul> <li>B-7561P</li> <li>Outdoor application</li> <li>Laminated</li> <li>Good UV-resistance</li> <li>High scratch resistance</li> <li>Good chemical resistance</li> <li>- 40°C to +120°C</li> <li>Up to 5 year durability</li> </ul>	<ul> <li>B-7562P</li> <li>Outdoor application</li> <li>Laminate with UV blocker</li> <li>High UV stability</li> <li>High scratch resistance</li> <li>Good chemical resistance</li> <li>- 40°C to +120°C</li> <li>Up to 8 year durability</li> </ul>

\*UL approved and BS5609 certified

#### All colour codes available:

Standard Brady colours (PIT)	Norwegian standard NS813
American standard ASME A13.1	German Standard DIN 2403
British Standard BS1710/4800	Swedish Standard SS741
Marine ISO 14726	Other: please provide the RAL/Pantone colours

Note: If you don't select a colour range we will deliver the pipe markers in Brady standard colours

#### Available formats:

Rolls

- Roll width: 150mm, 200mm, 225mm,
- 250mm, 400mm, 600mm
- Roll length: 15m, 30m, 50m
- Sheets (only with self-adhesive backing)
  - 150 x 12mm (5 markers on a sheet)
  - 250 x 26mm (4 markers on a sheet)
  - 355 x 37mm (3 markers on a sheet)
    450 x 52mm (2 markers on a sheet)

## Additional information

• GHS symbol(s)	Attachment
Warning symbol(s)	• Legend
Direction arrow(s)	Legend colour
Proof needed	Background colour

### Quantity

Provide the number of pipe markers you need to receive a quote.



# **Custom Pipe Marking**

Order check list

Order only the best pipe markers for your environment. Carefully consider the options below for maximum durability and return on investment. Contact Brady for more support.

### Available materials:

	INDOOR	OUTDOOR	OUTDOOR <sup>+</sup>
	B-7543P	B-7541P*	B-7529P
	<ul> <li>Indoor application</li> </ul>	<ul> <li>Outdoor application</li> </ul>	<ul> <li>Outdoor application</li> </ul>
	No laminate	Laminated	• Laminate with UV blocker
With	<ul> <li>Low UV-resistance</li> </ul>	Good UV-resistance	<ul> <li>High UV stability</li> </ul>
adhesive	• Medium scratch resistance	High scratch resistance	High scratch resistance
	• Medium chemical resistance	Good chemical resistance	Good chemical resistance
	<ul> <li>-40°C to +120°C</li> </ul>	<ul> <li>-40°C to +120°C</li> </ul>	<ul> <li>-40°C to +120°C</li> </ul>
	• 3 to 5 year durability	• Up to 5 year durability	• Up to 10 year durability
	B-7560P	B-7561P	B-7562P
	<ul> <li>Indoor application</li> </ul>	<ul> <li>Outdoor application</li> </ul>	<ul> <li>Outdoor application</li> </ul>
	No laminate	Laminated	<ul> <li>Laminate with UV blocker</li> </ul>
Without	<ul> <li>Low UV-resistance</li> </ul>	Good UV-resistance	High UV stability
adhesive	• Medium scratch resistance	High scratch resistance	High scratch resistance
	Medium chemical resistance	Good chemical resistance	Good chemical resistance
	<ul> <li>- 40°C to +120°C</li> </ul>	• - 40°C to +120°C	• - 40°C to +120°C
	• 3 to 5 year durability	• Up to 5 year durability	• Up to 8 year durability

\*UL approved and BS5609 certified

## All colour codes available:

• Standard Brady colours (PIT)	Norwegian standard NS813
American standard ASME A13.1	German Standard DIN 2403
British Standard BS1710/4800	Swedish Standard SS741
Marine ISO 14726	Other: please provide the RAL/Pantone colours

Note: If you don't select a colour range we will deliver the pipe markers in Brady standard colours

### **Available formats:**

- Rolls
  - Roll width: 150mm, 200mm, 225mm, 250mm, 400mm, • 600mm
  - Roll length: 15m, 30m, 50m •

• Sheets (only with self-adhesive backing)

VDOOR OV

- 150 x 12mm (5 markers on a sheet) •
- 250 x 26mm (4 markers on a sheet) •
- 355 x 37mm (3 markers on a sheet) •
- 450 x 52mm (2 markers on a sheet)

# Additional information

GHS symbol(s)	Attachment	3/02/
• Warning symbol(s)	• Legend	23
• Direction arrow(s)	Legend colour	_
Proof needed	Background colour	4 EV
		00

## Quantity

Provide the number of pipe markers you need to receive a quote.

2017